



## Spektrum™ SPMXAE1080 80 AMP AVIAN™ SMART ESC

Specifications	Specifications Cont. Current LiPo (		BEC Output	Size/Weight		
SPMXAE1080	80A	3–8S LiPo	6.0V/7.4V/8.4V@ 8A	83x35x33mm/ 145g		

Motor Wire and Connector	Battery Wire and Connector					
150mm / 12AWG / 4mm Bullet	150mm / 12AWG / Dual IC5 (series)					

Wiring Diagram
Throttle Connection
Receiver

Dual BEC/ RPM for Telemetry
(non Spektrum)
Battery\*
Battery\*

Other programming options include the SPMXCA200 Smart Avian ESC programming box and the SmartLink USB updating and programmer application. See SpektrumRC.com for more details about Avian ESCs.

Not Included
64620 Avian 80 Amp FSC SPM

Avian 80 Amp ESC SPMXAE1080

Programming Parameter	One short tone	Two short tones	Three short tones	Four short tones	One long tone	One long and one short tone	One long and two short tones	One long and three short tones
1. Aircraft Type (One Short Tone)	Airplane	Heli						
2. Brake Type (Two Short Tones)	Disabled	Normal	Pro- por- tional					
3. Brake Force (Three Short Tones)	Disabled	Level 1	Level 2	Level 3	Level 4	Level 5	Level 6	Level 7
4. Voltage Cutoff Type (Four Short Tones)	Soft	Hard						
5. Number Of Lipo Cells (One Long Tone)	Auto Calc.	3S	4S	5S	6S	8S		
6. Cutoff Voltage (One Long Tone And One Short Tone)	Disabled	2.8V	3.0V	3.2V	3.4V	3.6V	3.8V	
7. Bec Voltage (One Long Tone And Two Short Tones)	6.0V	7.4V	8.4V					
8. Start-Up Mode (One Long Tone And Three Short Tones)	Normal	Soft						
9. Timing (One Long Tone And Four Short Tones)	Low	Med	High					
10. Motor Rotation (Two Long Tones)	CW	CCW						
11. Freewheel Mode (Two Long Tones And One Short Tone)	Enabled	Disabled						
12. Factory Reset (Two Long Tones And Two Short Tones)								
13. Exit (Two Long Tons And A Series Of Short Tones)	Exit							