

X-Maxx® (Model 77086-4) Parts List

Parts shown in bold are optional accessories. Part categories and individual part listings are arranged alphabetically.

netric pitch)
netric pitch)
netric pitch)
S
33X spider gear shaft)
ear gasket/ 6x10x0.5 T\
reights)
8s)
s)
gears (4)/
y duty) (use with #779
y duty) (use with #7792
ueo with #7700 #770.
(use with #7790, #7791
imm TW (2)
stainless washer (2) (f
otaliliood wadiloi (2) (i
7750X driveshaft)
1130A univestiait)
y, shaft only, 160mm) (
4X and #7768, #7768F
(includes pins for 2
0X driveshaft)
for use only with
use only with #7750X
age only with #1100X
r use only with #7750X
,
se only with #7750X
k-anodized) (4)
nodized) (4)
anodized) (4)
-anodized) (4)
odized) (4)
ing
n, assembled with pivot
saver/ servo saver
•
avy duty (use with
, ,, (
r rear), heavy duty (1)
or rear), heavy duty (
, front or rear), heavy
rear), heavy duty (1)
or rear), heavy duty (1
r t,

Page 2	X-Maxx®: TQi Traxxas Link Enabled 2.4GHz Radio	& TSM ((Model 77086-4) Parts List
7831G	Suspension arm, green, lower (left, front or rear), heavy duty (1)	7760	Motor mounts (front and rear)/ pins (2)
7830G	Suspension arm, green, lower (right, front or rear), heavy duty	3491	Motor, Velineon® 1200XL, brushless
	(1)	2086	Servo case/gaskets (for 2085 & 2085X servos)
7831T	Suspension arm, orange, lower (left, front or rear), heavy duty (1)	2085	Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx®
7830T	Suspension arm, orange, lower (right, front or rear), heavy duty	2000	mount)
	(1)	2085X	Servo, digital high-torque, metal gear (ball bearing), waterproof/
7831R	Suspension arm, red, lower (left, front or rear), heavy duty (1)		servo saver spring/ steering link
7830R	Suspension arm, red, lower (right, front or rear), heavy duty (1)	3496	Velineon® VXL-8s Electronic Speed Control, waterproof (brushless)
7831A	Suspension arm, white, lower (left, front or rear), heavy duty (1)	0.00	(fwd/rev/brake)
7830A	Suspension arm, white, lower (right, front or rear), heavy duty (1)	7759	Washers, motor mount, aluminum (blue-anodized) (4)/ 4x18mm
7829X	Suspension arms, blue, upper (left or right, front or rear), heavy		BCS (4)
10237	duty (2)	7759G	Washers, motor mount, aluminum (green-anodized) (4)/ 4x18mm
7829G	Suspension arms, green, upper (left or right, front or rear), heavy		BCS (4)
70230	duty (2)	7759R	Washers, motor mount, aluminum (red-anodized) (4)/ 4x18mm
7731	Suspension arms, lower (left, front or rear) (1)		BCS (4)
7730	Suspension arms, lower (right, front or rear) (1)		Radio System, Batteries & Chargers
7829T	Suspension arms, orange, upper (left or right, front or rear),		
.020.	heavy duty (2)	2872X	5000mAh 11.1v 3-Cell 25C LiPo Battery
7829R	Suspension arms, red, upper (left or right, front or rear), heavy	2889X	5000mAh 14.8v 4-Cell 25C LiPo Battery
	duty (2)	2857X	6400mAh 11.1v 3-Cell 25C LiPo Battery
7729	Suspension arms, upper (left or right, front or rear) (2)	2890X	6700mAh 14.8v 4-Cell 25C LiPo Battery
7829A	Suspension arms, white, upper (left or right, front or rear), heavy	2938X	Adapter, Traxxas® iD® LiPo battery (adapts Traxxas iD batteries
	duty (2)		to separate balance ports)
7743	Suspension pin retainer (4)	2943	Battery charge indicators (green (4), blue (4), grey (4))
7740	Suspension pin set, front or rear corner (hardened steel), 4x85mm	6548	Battery door, transmitter (replacement for #6516, 6517, 6528, 6529,
	(1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set)		6530 transmitters)
7742	Suspension pin set, shock mount (front or rear, hardened steel),	2914	Battery, Power Cell AA Alkaline (4)
2	4x25mm (2), 4x38mm (2)	2990	Battery/charger completer pack (includes #2972 Dual iD®
7741	Suspension pins, 4x85mm (hardened steel) (2)		charger (1), #2872X 5000mAh 11.1V 3-cell 25C LiPo battery (2))
		2997	Battery/charger completer pack (includes #2973 Dual iD charger
	Hardware		(1), #2890X 6700mAh 14.8V 4-cell 25C LiPo battery (2))
2585	Cylinder head bolts, marine 3x20mm CS (6) (TRX 2.5)	2972	Charger, EZ-Peak® Dual, 100W, NiMH/LiPo with iD® Auto Battery
2584	Head screws, 3x12mm cap-head machine (hex drive) (6) (TRX 2.5,		Identification
	2.5R, 3.3)	2973	Charger, EZ-Peak® Live Dual, 200W, NiMH/LiPo with iD® Auto
2586	Head screws, 3x15mm cap-head machine (hex drive) (6) (TRX 2.5)		Battery Identification
4955	Pins, axle (2.5x12mm) (4)	2971	Charger, EZ-Peak® Live, 100W, NiMH/LiPo with iD® Auto Battery
3234	Screws, 2.5x14mm cap-head machine (hex drive) (6)		Identification
2577	Screws, 3x10mm button-head machine (hex drive) (6)	2970	Charger, EZ-Peak® Plus, 4 amp, NiMH/LiPo with iD® Auto
2587	Screws, 3x10mm cap-head machine (6) (no washer)		Battery Identification
4859	Screws, 3x10mm flat-head machine (hex drive) (4)	6525	Communication link, telemetry expander
2593	Screws, 3x14mm button-head machine (hex drive) (6)	2087	Gear set (for 2085 servo)
2579	Screws, 3x15mm button-head machine (hex drive) (6)	2087X	Gear set, metal (for 2085 & 2085X servos)
3646	Screws, 3x15mm flat-head machine (hex drive) (6)	2968X	LiPo cell voltage checker/balancer (includes #2938X adapter for
4857	Screws, 3x20mm countersunk machine (hex drive) (6)		Traxxas® iD® batteries)
2581	Screws, 3x25mm button-head machine (hex drive) (6)	2968	LiPo cell voltage checker/balancer (requires #2938X adapter for
2575	Screws, 3x6mm button-head machine (hex drive) (6)		Traxxas® iD® batteries)
2576	Screws, 3x8mm button-head machine (hex drive) (6)	6533	Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel)
2535	Screws, 4x10mm countersunk machine (hex drive) (6)	6552	Seal kit, expander box (includes o-ring, seals, and silicone
3937	Screws, 4x12mm button-head machine (hex drive) (6)		grease)
3938	Screws, 4x14mm button-head machine (hex drive) (6)	6526	Sensor, auto-detectable, temperature
2594	Screws, 4x15mm button-head machine (hex drive) (6)	6527	Sensor, auto-detectable, voltage
2546	Screws, 4x15mm countersunk machine (hex drive) (6)	6531	Sensor, temperature & voltage (fits X-Maxx®)
3933	Screws, 4x16mm button-head machine (hex drive) (6)	6521	Sensor, temperature and voltage (long)
2597	Screws, 4x22mm button-head machine (hex drive) (6)	2086	Servo case/gaskets (for 2085 & 2085X servos)
2596	, , , ,	2085	Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx®
	Screws, 4x25mm button-head machine (hex drive) (6)		mount)
2598X	Screws, 4x30mm button-head machine (hex drive) (6)	2085X	Servo, digital high-torque, metal gear (ball bearing), waterproof/
2595	Screws, 4x35mm button-head machine (hex drive) (6)		servo saver spring/ steering link
2743	Set (grub) screws, 3mm hardened (12)	6553X	Telemetry expander 2.0 and GPS module 2.0, TQi radio system
3642X	Shoulder screws, Ultra Shocks (3x12 hex drive) (6)	6550X	Telemetry expander 2.0, TQi radio system (for use only with
5480X	Wheel wrench, splined, 17mm		#6551X GPS module)
	LED Lights	6551X	Telemetry GPS module 2.0, TQi radio system (for use only with
7002	Extension harness, LED lights (high-voltage)		#6550X telemetry expander)
7882		6509R	TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™
6590	High-Voltage Power Amplifier		enabled, TSM (2-ch transmitter, 5-ch micro receiver)
7884	LED light bar, front (high-voltage) (40 white LEDs (double row),	6507R	TQi 2.4 GHz High Output radio system, 4-channel with Traxxas
7002	82mm wide) (fits X-Maxx® or Maxx®)		Link™ Wireless Module, TSM (4-ch transmitter, 5-ch micro
7883	LED light bar, rear, red (with white reverse light) (high-voltage)		receiver)
	(24 red LEDs, 24 white LEDs, 100mm wide)/ light bar mount (fits	6528	Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 2-
7005	X-Maxx® or Maxx®)		channel (transmitter only)
7885	LED light kit, complete (includes #6590 high-voltage power	6529	Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 3-
	amplifier)		channel (transmitter only)
	Motors & Electronics	6530	Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 4-
7749	Adapter, standard servo (adapts standard servo to fit in X-Maxx®		channel (transmitter only)
	or Maxx®)	6511	Traxxas Link™ Wireless Module
3475	Cooling fan, Velineon® VXL ESC (fits VXL-6s & VXL-8s)		Ready-To-Race Model
7787	Covers, gear (3)	77000	=
3474	Dual cooling fan kit (with shroud), Velineon® 1200XL motor	77086-4	X-Maxx®: Brushless Electric Monster Truck with TQi Traxxas Link™
2087	Gear set (for 2085 servo)		Enabled 2.4GHz Radio System & Traxxas Stability Management
2087X	Gear set, metal (for 2085 & 2085X servos)		(TSM)®
3362	Heat sink, Velineon® 1600XL		

Heat sink, Velineon® 1600XL

3362

Page 3	X-Maxx®:	TQi Traxxas	Link Enabled 2.4	GHz Radio & TSM	(Model 77086-4) Parts List
--------	----------	-------------	------------------	-----------------	----------------------------

	Rear Suspension	7761	Shocks, GTX, aluminum (blue-anodized) (fully assembled w/o springs) (2)
7726 7727X	Bulkhead tie bar, upper (1)/ lower (2) (steel) Bulkhead, rear (upper & lower), center differential (replacing #7727 &	7761G	Shocks, GTX, aluminum (green-anodized) (fully assembled w/o springs) (2)
	#7728 requires #5107A ball bearings (2))	7761R	Shocks, GTX, aluminum (red-anodized) (fully assembled w/o springs
752	Carriers, stub axle (left & right)		(2)
716	Mount, tie bar, front (1)/ rear (1)	1667	Silicone shock oil (30 wt), 60cc
738 831	Shock tower, rear (left & right halves) Suspension arm, black, lower (left, front or rear), heavy duty (1)	7767	Spring retainer (adjuster), blue-anodized aluminum, GTX shock
7830	Suspension arm, black, lower (right, front or rear), heavy duty (1)	7767G	(4) (assembled with o-ring) Spring retainer (adjuster), green-anodized aluminum, GTX
7829	Suspension arm, black, upper (left or right, front or rear), heavy	11010	shocks (4) (assembled with o-ring)
	duty (2)	7767X	Spring retainer (adjuster), PTFE-coated aluminum, GTX shocks
7831X	Suspension arm, blue, lower (left, front or rear), heavy duty (1)		(4) (assembled with o-ring)
7830X	Suspension arm, blue, lower (right, front or rear), heavy duty (1)	7767R	Spring retainer (adjuster), red-anodized aluminum, GTX shocks
7831G	Suspension arm, green, lower (left, front or rear), heavy duty (1)		(4) (assembled with o-ring)
7830G	Suspension arm, green, lower (right, front or rear), heavy duty	7853	Springs, shock (natural finish) (GTX) (0.824 rate) (2)
7831T	(1) Suspension arm, orange, lower (left, front or rear), heavy duty (1)	7854 7766	Springs, shock (natural finish) (GTX) (0.929 rate) (2)
7830T	Suspension arm, orange, lower (right, front or rear), heavy duty	7855	Springs, shock (natural finish) (GTX) (1.055 rate) (2) Springs, shock (natural finish) (GTX) (1.199 rate) (2)
	(1)	7856	Springs, shock (natural finish) (GTX) (1.135 rate) (2)
7831R	Suspension arm, red, lower (left, front or rear), heavy duty (1)	7857	Springs, shock (natural finish) (GTX) (1.450 rate) (2)
7830R	Suspension arm, red, lower (right, front or rear), heavy duty (1)	7858	Springs, shock (natural finish) (GTX) (1.538 rate) (2)
7831A	Suspension arm, white, lower (left, front or rear), heavy duty (1)		Spur Gears & Pinion Gears
7830A	Suspension arm, white, lower (right, front or rear), heavy duty (1)	C404V	<u>-</u>
7829X	Suspension arms, blue, upper (left or right, front or rear), heavy	6484X	Gear, 11-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (for use only with steel spur gears)
7829G	duty (2)	6485X	Gear, 12-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
1029G	Suspension arms, green, upper (left or right, front or rear), heavy duty (2)	0.0020	(for use only with steel spur gears)
7731	Suspension arms, lower (left, front or rear) (1)	6486X	Gear, 13-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
7730	Suspension arms, lower (right, front or rear) (1)		(for use only with steel spur gears)
7829T	Suspension arms, orange, upper (left or right, front or rear),	6488X	Gear, 14-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
	heavy duty (2)	6487X	Gear, 15-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
7829R	Suspension arms, red, upper (left or right, front or rear), heavy	6489X	Gear, 16-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
	duty (2)	6490X 6491X	Gear, 17-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
7729	Suspension arms, upper (left or right, front or rear) (2)	6494X	Gear, 18-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw Gear, 20-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
7829A	Suspension arms, white, upper (left or right, front or rear), heavy duty (2)	6495X	Gear, 22-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
7743	Suspension pin retainer (4)	6496X	Gear, 24-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
7740	Suspension pin set, front or rear corner (hardened steel), 4x85mm	6447R	Spur gear, 46-tooth, steel (wide-face, 1.0 metric pitch)
	(1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set)	6448R	Spur gear, 50-tooth, steel (wide-face, 1.0 metric pitch)
7742	Suspension pin set, shock mount (front or rear, hardened steel),	6449X	Spur gear, 54-tooth, steel (1.0 metric pitch)
	4x25mm (2), 4x38mm (2)	6449R	Spur gear, 54-tooth, steel (wide-face, 1.0 metric pitch)
7741	Suspension pins, 4x85mm (hardened steel) (2)		Steering Components
	Shock Oil	5119	Ball bearings, blue rubber sealed (10x15x4mm) (2)
5031	Oil, shock (20 wt, 200 cSt, 60cc) (silicone)	5116	Ball bearings, blue rubber sealed (5x11x4mm) (2)
5032	Oil, shock (30 wt, 350 cSt, 60cc) (silicone)	7747	Servo horn, steering/ linkage, steering (46mm, assembled with pivot
5033	Oil, shock (40 wt, 500 cSt, 60cc) (silicone)	77.40	balls)
5034 5035	Oil, shock (50 wt, 600 cSt, 60cc) (silicone) Oil, shock (60 wt, 700 cSt, 60cc) (silicone)	7746	Steering bellcranks/ bellcrank support/servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2)
5036	Oil, shock (70 wt, 900 cSt, 60cc) (silicone)	7746X	Steering link, steel/ servo saver spring, heavy duty (use with
5037	Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone)		#2085X metal gear servo)
5029	Shock oil bottle (60cc) (for mixing shock oil)	7748	Toe links, molded composite, 173mm (158mm center to center)
5038X	Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, &		(black) (2)
	80 wt premium shock oils with spinning carousel rack)	7748X	Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum,
1667	Silicone shock oil (30 wt), 60cc		stronger than titanium) (157mm) (2)/ rod ends, assembled with
5038	Spinning carousel rack	7748G	steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum
	Shocks (GTX)	1140G	stronger than titanium) (157mm) (2)/ rod ends, assembled with
765A	Body, GTX shock (aluminum, black-anodized) (1)		steel hollow balls (4)/ aluminum wrench, 10mm (1)
7765	Body, GTX shock (aluminum, blue-anodized) (1)	7748R	Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum,
7765G	Body, GTX shock (aluminum, green-anodized) (1)		stronger than titanium) (157mm) (2)/ rod ends, assembled with
7765R	Body, GTX shock (aluminum, red-anodized) (1)		steel hollow balls (4)/ aluminum wrench, 10mm (1)
765X	Body, GTX shock (hard-anodized, PTFE-coated aluminum) (1)		Suspension Linkage
7762	Rebuild kit, GTX shocks (lower cartridge, assembled, pistons, piston	7798	Insert, threaded steel (replacement inserts for #7748G, 7748R,
7700	nuts, bladders) (renews 2 shocks)	-	7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1)
7763	Shaft, GTX shock, 110mm (assembled with rod ends & hollow balls)		right threaded insert)
	(steel, chrome finish) (2)	7797	Rod ends (4) (assembled with steel pivot balls) (replacement
7763T			ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X)
7763T	Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and steel hollow balls)		Suspension pin retainer (4)
	shart, GTX shock, TIN-coated (2) (assembled with rod ends and steel hollow balls) Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers	7743 7740	Supposion nin set front or room corner (hardened steel) 4:05
	steel hollow balls)	7743 7740	Suspension pin set, front or rear corner (hardened steel), 4x85mm (1) 4x47mm (3) 4x33mm (2) (gtv 4 #7740 required for complete se
7764A	steel hollow balls) Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers (8) Shock caps, aluminum (green-anodized), GTX shocks (4)/	7740	(1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete se
7764A 7764G	steel hollow balls) Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers (8) Shock caps, aluminum (green-anodized), GTX shocks (4)/ spacers (8)		(1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete se Suspension pin set, shock mount (front or rear, hardened steel),
7764A 7764G	steel hollow balls) Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers (8) Shock caps, aluminum (green-anodized), GTX shocks (4)/ spacers (8) Shock caps, aluminum (hard-anodized, PTFE-coated), GTX	7740	(1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete se
7764A 7764G 7764X	steel hollow balls) Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers (8) Shock caps, aluminum (green-anodized), GTX shocks (4)/ spacers (8) Shock caps, aluminum (hard-anodized, PTFE-coated), GTX shocks (4)/ spacers (8)	7740 7742	(1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete se Suspension pin set, shock mount (front or rear, hardened steel), 4x25mm (2), 4x38mm (2)
7763T 7764A 7764G 7764X 7764R	steel hollow balls) Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers (8) Shock caps, aluminum (green-anodized), GTX shocks (4)/ spacers (8) Shock caps, aluminum (hard-anodized, PTFE-coated), GTX shocks (4)/ spacers (8) Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers	7740 7742 7741 7748	(1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete se Suspension pin set, shock mount (front or rear, hardened steel), 4x25mm (2), 4x38mm (2) Suspension pins, 4x85mm (hardened steel) (2) Toe links, molded composite, 173mm (158mm center to center) (black) (2)
7764A 7764G 7764X 7764R	steel hollow balls) Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers (8) Shock caps, aluminum (green-anodized), GTX shocks (4)/ spacers (8) Shock caps, aluminum (hard-anodized, PTFE-coated), GTX shocks (4)/ spacers (8) Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers (8)	7740 7742 7741	(1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete se Suspension pin set, shock mount (front or rear, hardened steel), 4x25mm (2), 4x38mm (2) Suspension pins, 4x85mm (hardened steel) (2) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum,
7764A 7764G 7764X 7764R	steel hollow balls) Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers (8) Shock caps, aluminum (green-anodized), GTX shocks (4)/ spacers (8) Shock caps, aluminum (hard-anodized, PTFE-coated), GTX shocks (4)/ spacers (8) Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers	7740 7742 7741 7748	(1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete se Suspension pin set, shock mount (front or rear, hardened steel), 4x25mm (2), 4x38mm (2) Suspension pins, 4x85mm (hardened steel) (2) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with
7764A 7764G 7764X	steel hollow balls) Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers (8) Shock caps, aluminum (green-anodized), GTX shocks (4)/ spacers (8) Shock caps, aluminum (hard-anodized, PTFE-coated), GTX shocks (4)/ spacers (8) Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers (8) Shock caps, GTX shocks/ spring perch/ adjusters/ 2.5x14mm CS (2)	7740 7742 7741 7748 7748X	(1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete se Suspension pin set, shock mount (front or rear, hardened steel), 4x25mm (2), 4x38mm (2) Suspension pins, 4x85mm (hardened steel) (2) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1)
7764A 7764G 7764X 7764R	steel hollow balls) Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers (8) Shock caps, aluminum (green-anodized), GTX shocks (4)/ spacers (8) Shock caps, aluminum (hard-anodized, PTFE-coated), GTX shocks (4)/ spacers (8) Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers (8) Shock caps, GTX shocks/ spring perch/ adjusters/ 2.5x14mm CS (2) (for 2 shocks)	7740 7742 7741 7748	(1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete se Suspension pin set, shock mount (front or rear, hardened steel), 4x25mm (2), 4x38mm (2) Suspension pins, 4x85mm (hardened steel) (2) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with

Page 4 X-Maxx®: TQi Traxxas Link Enabled 2.4GHz Radio & TSM (Model 77086-4) Parts List

Page 4	X-Maxx®: TQi Traxxas Link Enabled 2.4GHz Radio	& TSI
7748R	Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1)	7798
	Team Traxxas Items	
2514	Decal sheet, racing sponsors	7797
9950	Official Team Traxxas® racing decal set (flag logo/ 6-color)	1191
9909	Traxxas® racing banner, red & black (3x7 feet)	7748
	Tires & Wheels	
7772A	Tires & wheels, assembled, glued (X-Maxx® black chrome	7748X
	wheels, Maxx® AT tires, foam inserts) (left & right) (2)	
7772X	Tires & wheels, assembled, glued (X-Maxx® black wheels, Maxx® AT	7748G
7770	tires, foam inserts) (left & right) (2)	
7773	Tires & wheels, assembled, glued (X-Maxx® black wheels, paddle tires, foam inserts) (left & right) (2)	7748R
7772G	Tires & wheels, assembled, glued (X-Maxx® green wheels,	1140K
	Maxx® AT tires, foam inserts) (left & right) (2)	
7772T	Tires & wheels, assembled, glued (X-Maxx® orange wheels,	
7772R	Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® satin chrome	
11121	wheels, Maxx® AT tires, foam inserts) (left & right) (2)	
7770X	Tires, Maxx® AT (left & right) (2)/ foam inserts (2)	
7757	Wheel hex clips (6)	
7756	Wheel hubs, hex (2)/ hex clips (2)	
7756X 7756G	Wheel hubs, hex, aluminum (blue-anodized) (4) Wheel hubs, hex, aluminum (green-anodized) (4)	
7756R	Wheel hubs, hex, aluminum (green-anodized) (4)	
7758A	Wheel nuts, splined, 17mm, serrated (black-anodized) (4)	
7758	Wheel nuts, splined, 17mm, serrated (blue-anodized) (4)	
7758G	Wheel nuts, splined, 17mm, serrated (green-anodized) (4)	
7758T	Wheel nuts, splined, 17mm, serrated (orange-anodized) (4)	
7758R 5480X	Wheel nuts, splined, 17mm, serrated (red-anodized) (4) Wheel wrench, splined, 17mm	
7771	Wheels, X-Maxx®, black (left & right)	
	Transmission Components	
7706	-	
7796	Center drive, torque-biasing (assembled)/ 17x26x5 ball bearings (2) (requires #7727X bulkheads)	
7787	Covers, gear (3)	
7785X	Input gear, transmission, 20-tooth/ 2.5x12mm pin	
7786X	Input shaft, transmission (cush drive)	
5040 7784X	Oil, differential (20M wt) (standard) Output gear, 51-tooth, metal (requires #7785X input gear)	
11047	Traxxas Tools	
2422V		
3433X 3433	Body reamer (aluminum handle) Body reamer (plastic handle)	
3436	Cap, body reamer	
3432	Scissors, curved tip	
3431	Scissors, straight tip	
8712	Speed Bit Essentials Set, hex and nut driver, 7-piece, includes premium handle (medium), travel pouch, hex drivers (straight:	
	1.5mm, 2.0mm, 2.5mm) and nut drivers (5.0mm, 5.5mm, 7.0mm,	
	and 8.0mm), 1/4" drive	
8721	Speed bit handle, medium (one piece)	
8720	Speed bit handle, premium, large (rubber overmold)	
8722 8710	Speed bit handle, premium, medium (rubber overmold) Speed Bit Master Set, hex and nut driver, 13-piece, includes	
07.10	premium handle (medium), travel pouch, hex drivers (straight:	
	1.5mm, 2.0mm, 2.5mm, 3.0mm), (ball-end: 2.0mm, 2.5mm,	
	3.0mm), and nut drivers (4.00mm, 4.50mm, 5.00mm, 5.50mm,	
8711	7.00mm, 8.00mm), Speed Bit Master Set, hex driver, 7-piece straight and ball end,	
0711	includes premium handle (medium), travel pouch, hex drivers	
	(straight: 1.5mm, 2.0mm, 2.5mm, 3.0mm) (ball end: 2.0mm,	
0740	2.5mm, 3.0mm), 1/4" drive	
8719	Speed Bit Master Set, nut driver, 6-piece, includes premium handle (medium), travel pouch, and nut drivers (4.0mm, 4.5mm,	
	5.0mm, 5.5mm, 7.0mm, 8.0mm), 1/4" drive	
8716	Speed Bit Set, hex driver, 2-piece ball-end (2.0mm, 2.5mm), 1/4"	
0746V	drive	
8716X	Speed Bit Set, hex driver, 3-piece ball-end (2.0mm, 2.5mm, 3.0mm), 1/4" drive	
8715	Speed Bit Set, hex driver, 3-piece straight (1.5mm, 2.0mm,	
	2.5mm), 1/4" drive	
8715X	Speed Bit Set, hex driver, 4-piece straight (1.5mm, 2.0mm,	
3415	2.5mm, 3.0mm), 1/4" drive Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm,	
J-10	3.5mm, 4mm drivers/ 4mm, 5mm, 5.5mm, 7mm and 8mm nut	
	drivers/ 2mm, 4mm, and 5mm slotted screwdrivers/ #00 Phillips,	
	#0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrench/ driver handle	
5480Y	Wheel wrench enlined 17mm	

5480X

Wheel wrench, splined, 17mm

Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert)

Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X)

Toe links, molded composite, 173mm (158mm center to center) (black) (2)

Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum,

Turnbuckles & Threaded Rods

steel hollow balls (4)/ aluminum wrench, 10mm (1)
Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1)

stronger than titanium) (157mm) (2)/ rod ends, assembled with

7748R Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1)

If you have questions or need technical assistance, call Traxxas at:

1-888-TRAXXAS

(1-888-872-9927) (U.S. residents only)

For orders, calls outside the U.S., and other information, call 972-549-3000, or fax to 972-549-3011 e-mail Traxxas at support@Traxxas.com

TRAXXAS.COM